



XIAMEN JINGWEI TECHNOLOGY CO.,LTD.

Add: NO 58 Building, Yuemeijia Park, Jimei District, XIAMEN CHINA 361022

TEL: +86-0592-8628902

FAX: +86-592-6065010

www.cablecutting.net

Double feeding Wire Cutting and Stripping Machine (WPM-09F)

0.1-2.5sq.mm

Double feeding Wire 0.1-2.5sq. mm



Double feeding Wire Cutting and Stripping Machine (WPM-09F) 0.1-2.5sq.mm

Web link: <http://www.cablecutting.net/Dual-Wire-Cutting-and-Stripping-Machine.html>

Wire cross-section: 0.1-2.5sq.mm

Conduit diameter: 6mm

Stripping length: Head side 0-35mm

Tail side 0-15mm

Cutting length: 1-9999mm

Measurement: 39*35*25cm

Features:

Automatic Full Computer Wire Stripping Machine

Adopt the advanced automation technology from Japan,Taiwan.

It is a kind of numerical control equipment.

Apply for:

Widely used in the electronics industry, the city ahs, electrical appliances, motor, lamps, toys, and other various products of wire processing.

Optimal stripped wire PVC/teflon/silica gel line /. Glass fiber, etc.

Specification:

Available Wire Cross-Section Range:0.1~2.5mm²,double wires feeding and stripping

Conduit Diameter: \varnothing 6mm

Cutting Length:1~9999mm

Cutting Tolerance: $\pm(0.002 \times L)$ (L=Cutting Length)

Stripping Length: Head 0~35mm, Tail 0~15mm

Middle Stripping Section: Max 11

Speed: 5000-10000pcs/h

Display Way: English LCD display

Drive Mode: 4 Drives

Blade Material: Hard tungsten steel

Appropriate Wire: Electrical wires,PVC/Silica gel line/Glass fiber cables

Power Supply: 220V/50Hz 110V/60Hz

Power Rating: 200W

Measurement:390X350X255mm

Weight:32kg